




Plastic Insulating Bushings

- Polypropylene - Impact Resistant
- Temperature Rated at 105°
- Flame Retardant
- Threaded and used with locknut to terminate rigid or IMC conduit to box
- Smooth rounded surface prevents damage to wire insulation at raceway entrance



SPEC-grade



Plastic Insulated Bushings

Cat. #	Size	Unit Ctn	Std Pkg	WT/ 100
PIB50	1/2"	100	1000	1
PIB75	3/4"	100	500	2
PIB100	1"	50	250	2
PIB125	1-1/4"	-	100	2
PIB150	1-1/2"	-	100	2
PIB200	2"	-	50	3
PIB250	2-1/2"	-	25	4
PIB300	3"	-	25	5
PIB350	3-1/2"	-	25	7
PIB400	4"	-	20	8
PIB500	5"	-	5	10
PIB600	6"	-	5	11

Dimensional Table

Cat. #	A	B
PIB50	1.05	.36
PIB75	1.29	.40
PIB100	1.63	.49
PIB125	1.93	.48
PIB150	2.18	.48
PIB200	2.64	.54
PIB250	3.25	.63
PIB300	3.90	.68
PIB350	4.41	.68
PIB400	4.93	.68
PIB500	5.98	.77
PIB600	7.06	.77