




Made in the USA Since 1946

Rigid EMT Steel Straps

- To securely fasten and support Rigid or Intermediate metal conduit to the mounting surface
- For use in wet or dry locations
- Bright electro zinc finish for corrosion protection



One-Hole Rigid Type

Cat. #	Size	Unit Ctn	Std Pkg	WT/ 100
CSR251	1/4"	100	1000	2
CSR371	3/8"	100	1000	3
CSR501	1/2"	50	500	4
CSR751	3/4"	50	250	5
CSR1001	1"	50	250	8
CSR1251	1-1/4"	25	125	11
CSR1501	1-1/2"	20	100	17
CSR2001	2"	10	50	22
CSER2501	2-1/2"	-	20	42
CSER3001	3"	-	10	49
CSER3501	3-1/2"	-	10	71
CSER4001	4"	-	10	78

*Made in the USA

One-Hole BX Type

Cat. #	Size	Unit Ctn	Std Pkg	WT/ 100
CSBX381	12-2, 12-3, 10-2, 10-3	100	1000	1

Two-Hole Rigid Type

Cat. #	Size	Unit Ctn	Std Pkg	WT/ 100
CSR502*	1/2"	50	500	2
CSR752*	3/4"	50	250	3
CSR1002*	1"	50	250	5
CSR1252*	1-1/4"	25	125	7
CSR1502*	1-1/2"	20	100	12
CSR2002*	2"	10	50	15
CSER2502*	2-1/2"	-	20	17
CSER3002*	3"	-	10	23
CSER3502*	3-1/2"	-	10	26
CSER4002*	4"	-	10	33



Rigid IMC Conduit Fittings



EMT Steel Straps

- To securely fasten and support EMT metal conduit to the mounting surface
- For use in wet or dry locations
- Bright electro zinc finish for corrosion protection



One-Hole EMT Type

Cat. #	Size	Unit Ctn	Std Pkg	WT/100
CSE501	1/2"	100	1000	3
CSE751	3/4"	100	500	4
CSE1001	1"	50	250	6
CSE1251	1-1/4"	30	150	9
CSE1501	1-1/2"	25	125	13
CSE2001	2"	20	100	17
CSER2501	2-1/2"	-	20	42
CSER3001	3"	-	10	49
CSER3501	3-1/2"	-	10	71
CSER4001	4"	-	10	78

One-Hole BX Type

Cat. #	Size	Unit Ctn	Std Pkg	WT/100
CSBX381	12-2, 12-3, 10-2, 10-3	100	1000	1

Two-Hole EMT Type

Cat. #	Size	Unit Ctn	Std Pkg	WT/100
CSE502	1/2"	100	1000	2
CSE752	3/4"	100	500	3
CSE1002	1"	50	250	3
CSE1252	1-1/4"	30	150	6
CSE1502	1-1/2"	25	125	8
CSE2002	2"	15	75	14
CSER2502	2-1/2"	-	20	17
CSER3002	3"	-	10	23
CSER3502	3-1/2"	-	10	26
CSER4002	4"	-	10	33





Made in the USA Since 1946

Rigid Conduit Hangers with Bolts

- To fasten and secure EMT or rigid conduit to threaded rod, insulator supports, or directly to mounting surface
- Furnished with nut and bolt to accelerate installation
- For use in wet or dry locations
- Bright Electro Zinc Finish



Selection Table

Cat. #	Trade Size	Conduit Size		Unit / CTN	Std / Pkg	WT/100
		Rigid	EMT			
CHBOUS	0	3/8"-1/2"	1/2"	50	250	7
CHB1US	1	3/4"	3/4"	50	250	7
CHB2US	2	1"	1"	25	125	8
CHB25US	2-1/2	-	1-1/4"	20	100	11
CHB3US	3	1-1/4"	1-1/2"	20	100	11
CHB4 US	4	1-1/2"	-	10	50	19
CHB5 US	5	2"	2"	10	50	22
CHB6US	6	2-1/2"	2-1/2"	-	25	28
CHB7US	7	3"	3"	-	20	31
CHB8US	8	3-1/2"	3-1/2"	-	10	32
CHB9US	9	4"	4"	-	10	37

Rigid IMC Conduit Fittings



Made in the USA Since 1946

EMT CONDUIT:
Conduit Hangers with Bolts
Size Range: 3/8" - 1/2" to 4"

EMT Conduit Hangers with Bolts

- To fasten and secure EMT or rigid conduit to threaded rod, insulator supports, or directly to mounting surface
- Furnished with nut and bolt to accelerate installation
- For use in wet or dry locations
- Bright Electro Zinc finish



Selection Table


Cat. #	Trade Size	Conduit Size		Unit / CTN	Std / Pkg	WT/100
		Rigid	EMT			
CHBOUS	0	3/8"-1/2"	1/2"	50	250	7
CHB1US	1	3/4"	3/4"	50	250	7
CHB2US	2	1"	1"	25	125	8
CHB25US	2-1/2	-	1-1/4"	20	100	11
CHB3US	3	1-1/4"	1-1/2"	20	100	11
CHB4US	4	1-1/2"	-	10	50	19
CHB5US	5	2"	2"	10	50	22
CHB6US	6	2-1/2"	2 1/2"	-	25	28
CHB7US	7	3"	3"	-	20	31
CHB8US	8	3-1/2"	3-1/2"	-	10	32
CHB9US	9	4"	4"	-	10	37

EMT Conduit Fittings



Bus Drop Supports

- Galvanized steel mesh
- Permanent support
- Relieves tension and absorbs vibration



Cat. #	Cable Ranges		Length Eye	Length Mesh	Std Pkg	WT/ 100
	Min.	Max.				
BD032*	.220	.32	3	4.50	5	2
BD043*	.300	.43	4	5.13	10	2
BD056*	.410	.56	6	6.38	10	4
BD073*	.530	.73	7	8.00	10	5
BD085*	.700	.85	7	10.00	5	9
BD100*	.820	1.00	8	11.00	5	10
BD125*	.960	1.25	9	14.00	5	13
BD032UB**	.220	.32	9	4.50	5	2
BD043UB**	.300	.43	10	5.13	10	2
BD056UB**	.410	.56	12	6.38	10	5
BD073UB**	.530	.73	13	8.00	10	6
BD085UB**	.700	.85	13	16.00	5	11
BD100UB**	.820	1.00	14	11.00	5	13
BD125UB**	.960	1.25	15	14.00	5	16

* Single eye ** Universal Bail

Accessory Strain Relief Grips



Junior Pulling Grips

- Flexible eye
- High grade galvanized steel mesh
- Reusable




Cat. #	Cable Ranges		Length	Length	Std	WT/
	Min.	Max.	Eye	Mesh	Pkg	100
PJ024	19	.24	1/2"	4.25	1	2
PJ036	.25	.36	1/2"	7.00	1	2
PJ049	.34	.49	1/2"	10.12	1	3
PJ061	.50	.61	1/2"	11.75	1	6
PJ074	.62	.74	1/2"	13.25	1	10
PJ099	.75	.99	3/4"	14.00	1	15
PJ125	1.00	1.25	3/4"	15.87	1	23
PJK-1(KIT)	.25	1.25	-	-	1	85

Accessory Strain Relief Grips



Safety Springs

- High strength galvanized steel
- Available in 40 and 80 lb. test
- Used with single eye bus drops



Accessory Strain Relief Grips

Cat. #	Lbs.	Length	Diameter	Std Pkg	WT/ 100
SS40	40	8.25	.75	10	18
SS80	80	8.25	1.00	10	32