



GB Series Industrial SPEC-grade™ ALLOY STEEL Grounding Bushings Manufactured in the USA

Set Screw, Threaded or Threadless with Insulated Throat Available With or Without Optional Ground Lug

Furnished with 3 Pre-Drilled Holes and Set Screws

Unique Design Allows Ease of Installation and Orientation of Set Screw & Ground Lugs

Unique and Exclusive AMFICO Hex Nut Design Permits Industrial Grade Torque - **Locks Tight & Right**

Machined Alloy Steel - Zinc Plated or Galvanized Plated Product

Superior Life & Performance Over Zinc Die Cast & Malleable Iron Products

Furnished with UL Component Temperature Rated 150°C Insulated Throat

Available with Aluminum (*Standard*) Ground Lug or Optional Copper (CU) Ground Lug



NEVER CRACK ANOTHER BUSHING
TWICE the Tensile Strength & Brinell Hardness of Die Cast Products

Product Options for AMFICO SPEC-grade™ ALLOY STEEL USA Grounding Bushings

Trade Size	Material	Plating Options* 1.	Configurations 2.	Insulated Throat Option 3.	Lug Options 4.	Lug Material Options 5.	Wire Range Lug Size Options 6.
1/2"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14 - #4
3/4"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14 - #4 #8 - 1/0
1"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14 - #4 #8 - 1/0
1 1/4"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14 - #4 #8 - 1/0
1 1/2"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14 - #4 #8 - 1/0
2"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14 - #4 #8 - 1/0
2 1/2"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14-1/0 #6-250mcm
3"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14-1/0 #6-250mcm
3 1/2"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14-1/0 #6-250mcm
4"	Solid Alloy Steel	Z or G	T - NT	Y	Y	AL - CU	#14-1/0 #6-250mcm

Product Options Offered

1. Z = Zinc or G = Galvanized *Standard In-Stock Product is Zinc Plated
2. T = Threaded or NT = Threadless (No Threads Furnished with Set Screws)
3. Insulated Throat (Standard) Available Option for Non-Insulated Throat -Check NEC to Determine Requirement
4. Bushings Available with or Without Ground Lug
5. Ground Lug Material Options AL = Aluminum Lug in Sizes Shown or CU = Copper Lug in Sizes Shown
6. For Lug Sizes Not Shown, Consult Factory

Ground Bushings Are Furnished with an Insulated Throat Unless Specified Otherwise

