

# CG Straight Connector with Mesh SR

**Size Range:** 1/2" - 2"

**Product Series:** CGGT Cord Grip with Wire Mesh Strain Relief Grips

**Materials:** Connector Solid Alloy Steel Construction

Wire Mesh T316 Stainless Steel

**Grommet:** Santoprene, UL 94 V-0 FDA Approved

Fitting is Zinc Plated with a Chromate Finish

*Made in the USA*

**Features:**

Precision Machined Cut Threads NPT  
Solid Steel Construction

Connector Construction Provides Twice the Strength and Durability of ALL Die Cast and Malleable Products

UL Listed for use with flexible cords, including Type S, SO, STO, ST, SJ, SJT, SJTO and SVO.


## Industrial SPEC-grade

Ideal Uses:

- On-machine Wiring
- HVAC Applications
- Food Processing
- OEM Equipment
- Chemical Plants
- Mines
- Machine Tool Shops
- Motor Connections

Full FLAT HEX Surface with  
EZ Torque Steel Compression Nut &  
Steel Compression Ring  
Torques Tight & Right On Cord

Suitable for Wet Locations When a Sealing Washer is Used Between  
Connector;s NPT Threads and NPT Threaded Enclosure. For Non-Threaded Enclosures  
The Addition of a Locknut and Sealing Washer are Required, Sold Separately.



Easily Installed on .250" to 2.60" Cable Diameter Range  
1/2" to 2" Hub - See Chart Pg 2



**Compliances:**

- Certified Made in the USA
- UL 514 B, 467
- Grommet is UL Rated 94V0 and UL94 5KVA FDA Approved
- NEMA Standard FB1
- Rated NEMA Types 2, 3, 3R, 3, 4X, 5, 12, 13
- NEC: Class I, Division 2
- Class II, Divisions 1 and 2
- Class III, Divisions 1 and 2
- Federal Standard A-A-50553
- UL Rated for Wet Locations
- CSA Standard: C22.2 No. 18F
- RoHS Compliant
- REACH Compliant
- CA Prop 65 Compliant
- UNSPSC 39123033



**Features:**

- Indoor & Outdoor Applications
- NPT Straight Male Thread
- Single Weave Variable Stainless Steel Mesh
- Provides additional Holding Power In Abrasive Environments
- One-Piece Design Mesh Integrated into Connector Body
- Water Tight & Dust-Tight Seal

**Optional:**

- Insulating Throat Bushing 105° c Rated
- Industrial Grade Steel Locknuts and Sealing Washers


# CG Straight Connector with Mesh SR

Since 1946

Size Range: 1/2" - 2"

Industrial SPEC-grade

Product Series: CGGT Cord Grip with Wire Mesh Strain Relief Grips



| Cat #        | Trade Size | Cable Ranges |       | A Length | B Diameter | C Mesh Length | D NPT Thread Length | Wt. Per/C |
|--------------|------------|--------------|-------|----------|------------|---------------|---------------------|-----------|
|              |            | Min          | Max   |          |            |               |                     |           |
| CG50A250GT   | 1/2"       | .150         | .250  | 2"       | 1-5/8"     | 4-1/2"        | 1/2"                | 12        |
| CG50A350GT   | 1/2"       | .250         | .350  | 2"       | 1-5/8"     | 4-1/2"        | 1/2"                | 12        |
| CG50A450GT   | 1/2"       | .350         | .450  | 2"       | 1-5/8"     | 4-1/2"        | 1/2"                | 12        |
| CG50A560GT   | 1/2"       | .450         | .560  | 2"       | 1-5/8"     | 4-1/2"        | 1/2"                | 12        |
| CG50A650GT   | 1/2"       | .560         | .650  | 2"       | 1-5/8"     | 4-1/2"        | 1/2"                | 12        |
| CG75A250GT   | 3/4"       | .150         | .250  | 2-3/16"  | 1-1/4"     | 4-1/2"        | 9/16"               | 16        |
| CG75A350GT   | 3/4"       | .250         | .350  | 2-3/16"  | 1-1/4"     | 4-1/2"        | 9/16"               | 16        |
| CG75A450GT   | 3/4"       | .350         | .450  | 2-3/16"  | 1-1/4"     | 4-1/2"        | 9/16"               | 16        |
| CG75A560GT   | 3/4"       | .450         | .560  | 2-3/16"  | 1-1/4"     | 4-1/2"        | 9/16"               | 16        |
| CG75A650GT   | 3/4"       | .560         | .650  | 2-3/16"  | 1-1/4"     | 4-1/2"        | 9/16"               | 16        |
| CG75B750GT   | 3/4"       | .650         | .750  | 2-3/16"  | 1-3/8"     | 9-1/2"        | 9/16"               | 26        |
| CG75B850GT   | 3/4"       | .750         | .850  | 2-3/16"  | 1-3/8"     | 9-1/2"        | 9/16"               | 26        |
| CG100B560GT  | 1"         | .450         | .560  | 2"       | 1-1/2"     | 6"            | 11/16"              | 30        |
| CG100B650GT  | 1"         | .560         | .650  | 2"       | 1-1/2"     | 6"            | 11/16"              | 30        |
| CG100B750GT  | 1"         | .650         | .750  | 2"       | 1-1/2"     | 6"            | 11/16"              | 30        |
| CG100B850GT  | 1"         | .750         | .850  | 2"       | 1-1/2"     | 6"            | 11/16"              | 30        |
| CG100C950GT  | 1"         | .850         | .950  | 2-1/16"  | 1-5/8"     | 9-1/2"        | 5/8"                | 36        |
| CG100C1050GT | 1"         | .950         | 1.050 | 2-1/16"  | 1-5/8"     | 9-1/2"        | 5/8"                | 36        |
| CG125C850GT  | 1-1/4"     | .750         | .850  | 2-1/8"   | 1-7/8"     | 9"            | 11/16"              | 49        |
| CG125C950GT  | 1-1/4"     | .850         | .950  | 2-1/8"   | 1-7/8"     | 9"            | 11/16"              | 49        |
| CG125D1050GT | 1-1/4"     | .950         | 1.050 | 2-5/16"  | 2-1/16"    | 9-1/2"        | 11/16"              | 52        |
| CG125D1150GT | 1-1/4"     | 1.050        | 1.150 | 2-5/16"  | 2-1/16"    | 9-1/2"        | 11/16"              | 52        |
| CG125D1250GT | 1-1/4"     | 1.150        | 1.250 | 2-5/16"  | 2-1/16"    | 9-1/2"        | 11/16"              | 52        |
| CG125D1375GT | 1-1/4"     | 1.250        | 1.375 | 2-5/16"  | 2-1/16"    | 9-1/2"        | 11/16"              | 52        |
| CG150D1050GT | 1-1/2"     | .950         | 1.050 | 2-7/16"  | 2-3/8"     | 9-1/2"        | 11/16"              | 76        |
| CG150D1150GT | 1-1/2"     | 1.050        | 1.150 | 2-7/16"  | 2-3/8"     | 9-1/2"        | 11/16"              | 76        |
| CG150D1250GT | 1-1/2"     | 1.150        | 1.250 | 2-7/16"  | 2-3/8"     | 9-1/2"        | 11/16"              | 76        |
| CG150D1375GT | 1-1/2"     | 1.250        | 1.375 | 2-7/16"  | 2-3/8"     | 9-1/2"        | 11/16"              | 76        |
| CG150E1500GT | 1-1/2"     | 1.380        | 1.500 | 2-3/8"   | 2-3/8"     | 12"           | 3/4"                | 78        |
| CG150E1630GT | 1-1/2"     | 1.500        | 1.630 | 2-3/8"   | 2-3/8"     | 12"           | 3/4"                | 78        |
| CG150E1750GT | 1-1/2"     | 1.630        | 1.750 | 2-3/8"   | 2-3/8"     | 12"           | 3/4"                | 78        |
| CG150E1880GT | 1-1/2"     | 1.750        | 1.880 | 2-3/8"   | 2-3/8"     | 12"           | 3/4"                | 78        |
| CG200F1380GT | 2"         | 1.250        | 1.380 | 2-13/16" | 2-7/8"     | 12"           | 3/4"                | 124       |
| CG200F1500GT | 2"         | 1.380        | 1.500 | 2-13/16" | 2-7/8"     | 12"           | 3/4"                | 124       |
| CG200F1630GT | 2"         | 1.500        | 1.630 | 2-13/16" | 2-7/8"     | 12"           | 3/4"                | 124       |
| CG200F1750GT | 2"         | 1.630        | 1.750 | 2-13/16" | 2-7/8"     | 12"           | 3/4"                | 124       |
| CG200F1810GT | 2"         | 1.690        | 1.810 | 2-13/16" | 2-7/8"     | 14"           | 3/4"                | 124       |
| CG200F1880GT | 2"         | 1.750        | 1.880 | 2-13/16" | 2-7/8"     | 14"           | 3/4"                | 124       |
| CG200F1940GT | 2"         | 1.810        | 1.940 | 2-13/16" | 2-7/8"     | 14"           | 3/4"                | 124       |
| CG200F2060GT | 2"         | 1.940        | 2.060 | 2-13/16" | 2-7/8"     | 14"           | 3/4"                | 124       |

# CG 90° Connector with Mesh SR

Size Range: 1/2" - 1"

Product Series: CGGT Cord Grip with Wire Mesh Strain Relief Grips

Materials: Body MI Compression Nut Steel Construction

Wire Mesh T316 Stainless Steel

Grommet: Santoprene, UL 94 V-0 FDA Approved

Fitting is Zinc Plated

*Made in the USA*

**Features:**

Precision Machined Cut Threads NPT

Solid Steel Construction

## Industrial SPEC-grade


**Ideal Uses:**

- On-machine Wiring
- HVAC Applications
- Food Processing
- OEM Equipment
- Chemical Plants
- Mines
- Machine Tool Shops
- Motor Connections

UL Listed for use with flexible cords, including Type S, SO, STO, ST, SJ, SJT, SJTO and SVO.

Full FLAT HEX Surface with  
EZ Torque Steel Compression Nut &  
Steel Compression Ring  
Torques Tight & Right On Cord

Suitable for Wet Locations When  
A Sealing Washer is Used Between Connectors NPT Threads and an NPT Threaded Enclosure.  
For Non-Threaded Enclosures, Use a Locknut and Sealing Washer are Required, Sold Separately.



Easily Installed on .250" to 1.050" Cable Diameter Range  
1/2" to 1" Hub - See Chart Pg 2

**Compliances:**

Certified Made in the USA

UL 514 B, 467

Grommet is UL Rated 94V0 and UL94 5KVA FDA Approved

NEMA Standard FB1

Rated NEMA Types 2, 3, 3R, 3, 4X, 5, 12, 13

NEC: Class I, Division 2

Class II, Divisions 1 and 2

Class III, Divisions 1 and 2

Federal Standard A-A-50553

UL Rated for Wet Locations

CSA Standard: C22.2 No. 18F

RoHS Compliant

REACH Compliant

CA Prop 65 Compliant

UNSPSC 39123033



**Features:**

For Use Indoor & Outdoor Applications

NPT Straight Male Thread

Single Weave Variable Stainless Steel Mesh

Provides additional Holding Power In Abrasive Environments

One-Piece Design Mesh Integrated into Connector Body

Water Tight & Dust-Tight Seal

**Optional:**

Insulating Throat Bushing 105° c Rated


Industrial Grade Steel Locknuts and Sealing Washers

# CG 90° Connector with Mesh SR

Size Range: 1/2" - 1"

Product Series: CGGT Cord Grip with Wire Mesh Strain Relief Grips

Industrial SPEC-grade



| Cat #          | Trade Size | Cable Ranges |       | A Length | B Height | C Diameter | D Mesh Length | E NPT Thread Length | Wt. Per/C |
|----------------|------------|--------------|-------|----------|----------|------------|---------------|---------------------|-----------|
|                |            | Min          | Max   |          |          |            |               |                     |           |
| CG50A25090GT   | 1/2"       | .150         | .250  | 2-9/16"  | 1-7/8"   | 1-3/16"    | 4-1/2"        | 5/8"                | 28        |
| CG50A35090GT   | 1/2"       | .250         | .350  | 2-9/16"  | 1-7/8"   | 1-3/16"    | 4-1/2"        | 5/8"                | 28        |
| CG50A45090GT   | 1/2"       | .350         | .450  | 2-9/16"  | 1-7/8"   | 1-3/16"    | 4-1/2"        | 5/8"                | 28        |
| CG50A56090GT   | 1/2"       | .450         | .560  | 2-9/16"  | 1-7/8"   | 1-3/16"    | 4-1/2"        | 5/8"                | 28        |
| CG50A65090GT   | 1/2"       | .560         | .650  | 2-9/16"  | 1-7/8"   | 1-3/16"    | 4-1/2"        | 5/8"                | 28        |
| CG75A25090GT   | 3/4"       | .150         | .250  | 2-3/4"   | 2-1/4"   | 1-7/16"    | 5-1/2"        | 5/8"                | 44        |
| CG75A35090GT   | 3/4"       | .250         | .350  | 2-3/4"   | 2-1/4"   | 1-7/16"    | 5-1/2"        | 5/8"                | 44        |
| CG75A45090GT   | 3/4"       | .350         | .450  | 2-3/4"   | 2-1/4"   | 1-7/16"    | 5-1/2"        | 5/8"                | 44        |
| CG75A56090GT   | 3/4"       | .450         | .560  | 2-3/4"   | 2-1/4"   | 1-7/16"    | 5-1/2"        | 5/8"                | 44        |
| CG75A65090GT   | 3/4"       | .560         | .650  | 2-3/4"   | 2-1/4"   | 1-7/16"    | 5-1/2"        | 5/8"                | 44        |
| CG75B75090GT   | 3/4"       | .650         | .750  | 2-3/4"   | 2-1/4"   | 1-7/16"    | 9"            | 11/16"              | 40        |
| CG75B85090GT   | 3/4"       | .750         | .850  | 2-3/4"   | 2-1/4"   | 1-7/16"    | 9"            | 11/16"              | 40        |
| CG100B56090GT  | 1"         | .450         | .560  | 3-3/16"  | 2-3/4"   | 1-13/16"   | 6-1/2"        | 11/16"              | 74        |
| CG100B65090GT  | 1"         | .560         | .650  | 3-3/16"  | 2-3/4"   | 1-13/16"   | 6-1/2"        | 11/16"              | 74        |
| CG100B75090GT  | 1"         | .650         | .750  | 3-3/16"  | 2-3/4"   | 1-13/16"   | 6-1/2"        | 11/16"              | 74        |
| CG100B85090GT  | 1"         | .750         | .850  | 3-3/16"  | 2-3/4"   | 1-13/16"   | 6-1/2"        | 11/16"              | 74        |
| CG100C95090GT  | 1"         | .850         | .950  | 3-5/8"   | 2-3/4"   | 1-13/16"   | 7-1/2"        | 11/16"              | 74        |
| CG100C105090GT | 1"         | .950         | 1.050 | 3-5/8"   | 2-3/4"   | 1-13/16"   | 7-1/2"        | 11/16"              | 74        |

# CG 45° Connector with Mesh SR

Size Range: 1/2" - 1"

Product Series: CGGT Cord Grip with Wire Mesh Strain Relief Grips

Materials: Body MI Compression Nut Steel Construction  
Wire Mesh T316 Stainless Steel

Grommet: Santoprene, UL 94 V-0 FDA Approved

Fitting is Zinc Plated

*Made in the USA*

**Features:**

Precision Machined Cut Threads NPT  
Solid Steel Construction

## Industrial SPEC-grade


**Ideal Uses:**

- On-machine Wiring
- HVAC Applications
- Food Processing
- OEM Equipment
- Chemical Plants
- Mines
- Machine Tool Shops
- Motor Connections


UL Listed for use with flexible cords, including Type S, SO, STO, ST, SJ, SJT, SJTO and SVO.

Full FLAT HEX Surface with  
EZ Torque Steel Compression Nut &  
Steel Compression Ring  
Torques Tight & Right On Cord

Suitable for Wet Locations When  
A Sealing Washer is Used Between Connectors NPT Threads and an NPT Threaded Enclosure.  
For Non-Threaded Enclosures, Use a Locknut and Sealing Washer are Required, Sold Separately.



Easily Installed on .250" to 1.050" Cable Diameter Range  
1/2" to 1" Hub - See Chart Pg 2



**Compliances:**

- Certified Made in the USA
- UL 514 B, 467
- Grommet is UL Rated 94V0 and UL94 5KVA FDA Approved
- NEMA Standard FB1
- Rated NEMA Types 2, 3, 3R, 3, 4X, 5, 12, 13
- NEC: Class I, Division 2
- Class II, Divisions 1 and 2
- Class III, Divisions 1 and 2
- Federal Standard A-A-50553
- UL Rated for Wet Locations
- CSA Standard: C22.2 No. 18F
- RoHS Compliant
- REACH Compliant
- CA Prop 65 Compliant
- UNSPSC 39123033

**Features:**

- For Use Indoor & Outdoor Applications
- NPT Straight Male Thread
- Single Weave Variable Stainless Steel Mesh
- Provides additional Holding Power In Abrasive Environments
- One-Piece Design Mesh Integrated into Connector Body
- Water Tight & Dust-Tight Seal

**Optional:**


- Insulating Throat Bushing 105° c Rated
- Industrial Grade Steel Locknuts and Sealing Washers

# CG 45° Connector with Mesh SR

Size Range: 1/2" - 1" Page 2 Dimensions

Product Series: CGGT Cord Grip with Wire Mesh Strain Relief Grips

Industrial SPEC-grade



| Cat #          | Trade Size | Cable Ranges |       | A Length | B Height | C Diameter | D Mesh Length | E Thread Length | Wt. Per/C |
|----------------|------------|--------------|-------|----------|----------|------------|---------------|-----------------|-----------|
|                |            | Min          | Max   |          |          |            |               |                 |           |
| CG50A25045GT   | 1/2"       | .150         | .250  | 2-5/8"   | 1-11/16" | 1-3/16"    | 4-1/2"        | 5/8"            | 25        |
| CG50A35045GT   | 1/2"       | .250         | .350  | 2-5/8"   | 1-11/16" | 1-3/16"    | 4-1/2"        | 5/8"            | 25        |
| CG50A45045GT   | 1/2"       | .350         | .450  | 2-5/8"   | 1-11/16" | 1-3/16"    | 4-1/2"        | 5/8"            | 25        |
| CG50A56045GT   | 1/2"       | .450         | .560  | 2-5/8"   | 1-11/16" | 1-3/16"    | 4-1/2"        | 5/8"            | 25        |
| CG50A65045GT   | 1/2"       | .560         | .650  | 2-5/8"   | 1-11/16" | 1-3/16"    | 4-1/2"        | 5/8"            | 25        |
| CG75A25045GT   | 3/4"       | .150         | .250  | 2-3/4"   | 2"       | 1-7/16"    | 4-1/2"        | 5/8"            | 36        |
| CG75A35045GT   | 3/4"       | .250         | .350  | 2-3/4"   | 2"       | 1-7/16"    | 4-1/2"        | 5/8"            | 36        |
| CG75A45045GT   | 3/4"       | .350         | .450  | 2-3/4"   | 2"       | 1-7/16"    | 4-1/2"        | 5/8"            | 36        |
| CG75A56045GT   | 3/4"       | .450         | .560  | 2-3/4"   | 2"       | 1-7/16"    | 4-1/2"        | 5/8"            | 36        |
| CG75A65045GT   | 3/4"       | .560         | .650  | 2-3/4"   | 2"       | 1-7/16"    | 4-1/2"        | 5/8"            | 36        |
| CG75B75045GT   | 3/4"       | .650         | .750  | 2-3/4"   | 2"       | 1-7/16"    | 9"            | 5/8"            | 34        |
| CG75B85045GT   | 3/4"       | .750         | .850  | 2-3/4"   | 2"       | 1-7/16"    | 9"            | 5/8"            | 34        |
| CG100B56045GT  | 1"         | .450         | .560  | 3-1/8"   | 2-1/4"   | 1-3/4"     | 6-1/2"        | 11/16"          | 63        |
| CG100B65045GT  | 1"         | .560         | .650  | 3-1/8"   | 2-1/4"   | 1-3/4"     | 6-1/2"        | 11/16"          | 63        |
| CG100B75045GT  | 1"         | .650         | .750  | 3-1/8"   | 2-1/4"   | 1-3/4"     | 6-1/2"        | 11/16"          | 63        |
| CG100B85045GT  | 1"         | .750         | .850  | 3-1/8"   | 2-1/4"   | 1-3/4"     | 6-1/2"        | 11/16"          | 63        |
| CG100C95045GT  | 1"         | .850         | .950  | 3-1/2"   | 2-1/4"   | 1-3/4"     | 7-1/2"        | 11/16"          | 64        |
| CG100C105045GT | 1"         | .950         | 1.050 | 3-1/2"   | 2-1/4"   | 1-3/4"     | 7-1/2"        | 11/16"          | 64        |

## CG Wide Range Grip with Mesh SR

Size Range: 1/2" - 2 1/2"

Product Series: SR Cord Grip with Wire Mesh Strain Relief Grips

Materials: Connector - Aluminum Construction  
Wire Mesh - Galvanized Steel

*Made in the USA*

**Features:**

Precision Machined Cut Threads NPT  
Copper Free Aluminum  
Neoprene Sealing Grommet




### Industrial SPEC-grade

Ideal Uses:

- On-machine Wiring
- HVAC Applications
- Food Processing
- OEM Equipment
- Chemical Plants
- Mines
- Machine Tool Shops
- Motor Connections

Wide-range grips are recommended for use in the wiring of enclosures, power boxes, machine tools, and power centers. They have an anodized aluminum body, galvanized steel mesh with an insulated bushing and industrial grade locknut.

UL Listed for use with flexible cords, including Type S, SO, STO, ST, SJ, SJT, SJTO and SVO.



NPT

Easily Installed on .220" to 2.45" Cable Diameter Range  
1/2" to 2 1/2" Hub

Wide Range Series has a male NPT thread and can be fitting with an Optional industrial-grade steel locknut for thru hole enclosures up to 3/8" thick.

**Compliances:**

Certified Made in the USA  
UL 514 B, 467  
NEMA Standard FB1

CSA Standard: C22.2 No. 18F  
RoHS Compliant  
REACH Compliant  
CA Prop 65 Compliant  
UNSPSC 39123033

**Features:**

For Use Indoor Applications Only  
NPT Straight Male Thread  
Single Weave Variable Galvanized Steel Mesh  
Provides additional Holding Power In Abrasive Environments  
One-Piece Design Mesh Integrated into Connector Body

**Optional:**

\* Insulating Throat Bushing 105° c Rated -see pg 2 chart

Steel Locknut




# CG Wide Range Grip with Mesh SR

Size Range: 1/2" - 2 1/2"

Industrial SPEC-grade

Product Series: SR Wide Range Cord Grip with Wire Mesh Strain Relief Grips



| Cat #    | Trade Size | Cable Ranges |       | A Length | B Diameter | C Mesh Length | D NPT Length Thread |
|----------|------------|--------------|-------|----------|------------|---------------|---------------------|
|          |            | MIN          | MAX   |          |            |               |                     |
| SR001    | 1/2"       | .220         | .320  | 15/16"   | 1-1/32"    | 4"            | 1/2"                |
| SR002    | 1/2"       | .300         | .430  | 15/16"   | 1-1/32"    | 5-1/4"        | 1/2"                |
| SR003    | 1/2"       | .400         | .540  | 15/16"   | 1-1/32"    | 7"            | 1/2"                |
| SR004    | 3/4"       | .520         | .730  | 1"       | 1-3/8"     | 8-1/2"        | 19/32"              |
| SR005    | 1"         | .700         | .970  | 1-7/32"  | 1-5/8"     | 10"           | 3/4"                |
| SR006    | 1-1/4"     | .940         | 1.200 | 1-7/16"  | 2-1/8"     | 13"           | 3/4"                |
| SRB008 * | 1-2"       | .220         | .320  | 1-9/16"  | 1-1/32"    | 4"            | 1"                  |
| SRB009 * | 1-2"       | .300         | .430  | 1-9/16"  | 1-1/32"    | 5-1/4"        | 1"                  |
| SRB010 * | 1-2"       | .400         | .540  | 1-9/16"  | 1-1/32"    | 6-3/4"        | 1"                  |
| SRB011 * | 3/4"       | .520         | .730  | 1-9/16"  | 1-3/8"     | 8-1/2"        | 1"                  |
| SRB012 * | 1"         | .700         | .970  | 1-7/8"   | 1-5/8"     | 10"           | 1-1/4"              |
| SRB013 * | 1-1/4"     | .940         | 1.250 | 2-1/8"   | 2-1/8"     | 13"           | 1-1/4"              |
| SRB014 * | 1-1/2"     | 1.200        | 1.500 | 2-1/8"   | 2-1/4"     | 15-1/4"       | 1-1/4"              |
| SRB015 * | 2"         | 1.400        | 1.750 | 2-9/32"  | 2-25/32"   | 17-3/4"       | 1-3/8"              |
| SRB016 * | 2-1/2"     | 1.620        | 2.000 | 2-7/8"   | 3-1/4"     | 20-1/2"       | 1-1/2"              |
| SRB017 * | 2-1/2"     | 2.000        | 2.450 | 2-7/8"   | 3-1/4"     | 22"           | 1-1/2"              |

\* Includes Insulating Throat Bushing



Compliances and Other Info Shown on Page 1